

# Amoladora Angular GWS 17-125 PS

|     |                  |
|-----|------------------|
| SKU | 0601.7D1.3E0-000 |
| EAN | 4059952576688    |



## Alcance de la entrega

|                                                        |   |
|--------------------------------------------------------|---|
| Cardboard box                                          | ✓ |
| Vibration Control auxiliary handle (2 608 900 000)     | ✓ |
| Protective guard (1 605 510 365)                       | ✓ |
| Protective clip-on cutting guard metal (2 608 000 756) | ✓ |
| Two-hole spanner (1 607 950 043)                       | ✓ |
| Backing flange (1 605 703 099)                         | ✓ |
| Locking nut (1 603 340 040)                            | ✓ |
| Dust filter (2 608 000 824)                            | ✓ |

## Datos técnicos

|                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Perforación, Ø                      | 22,230                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Peso                                | 2,200                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Empuñadura principal                | Barrel                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Velocidad en vacío                  | 2,800 – 11,500 rpm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Velocidad de giro en vacío, hasta   | 11.500,0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Velocidad de giro en vacío, desde   | 2.800,0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Potencia absorbida                  | 1.700,0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Interruptor                         | PROtection Switch                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Ø del disco                         | 125,0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Rosca del husillo portamuela        | M14                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Versión larga parte 1               | The GWS 17-125 PS Professional with Speed Selection provides maximum convenience during application thanks to the ergonomic and slim grip design. The PROtection switch immediately shuts off the angle grinder as soon as the switch is released. Its high power and robustness, and the improved dust protection by air inlets at the backside of the tool, ensure maximum productivity. Additional user protection is provided by features like KickBack Control, Restart Protection, and Vibration Control side handle.                                                |
| Versión larga parte 2               | The small angle grinder is best for grinding metal or welding seams and cutting metal, concrete, bricks, and tiles. It is compatible with Bosch’s dust extraction systems GDE 125 EA-T Professional and GDE 115 / 125 FC-T Professional.                                                                                                                                                                                                                                                                                                                                   |
| Versión larga parte 3               | Speed Selection, Constant Speed, Soft Start, and Overload Protection are additional features.                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Información adicional versión corta | Speed Selection, Constant Speed, Soft Start, and removable dust filter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Tolerancia K                        | 3,0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Nivel de presión acústica           | 94,0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Nivel de ruido                      | The A-rated noise level of the power tool is typically as follows: Sound pressure level 94 dB(A); Sound power level 102 dB(A). Uncertainty K= 3 dB.                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Nivel total de vibraciones          | 1,500<br>5,500<br>Lijar con hoja de lija<br>Desbastar superficies (desbastado)<br>3,200                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Versión larga parte 1 (BE)          | La GWS 17-125 PS con Speed Selection ofrece la máxima comodidad durante su uso gracias al diseño ergonómico y delgado de su zona de agarre. El interruptor PROtection desconecta inmediatamente la amoladora en cuanto se suelta el interruptor. Su alta potencia y robustez, y la protección mejorada contra el polvo mediante rejillas de ventilación en la parte trasera de la herramienta, garantizan la máxima productividad. Protección adicional del operador gracias a funciones como KickBack Control, Restart Protection y empuñadura lateral Vibration Control. |
| Nivel de potencia acústica          | 102,0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Versión larga parte 2 (BE)          | La amoladora pequeña es la mejor para lijar metal o cordones de soldadura y cortar metal, concreto, ladrillos y baldosa. Es compatible con los sistemas de aspiración GDE 125 EA-T y GDE 115 / 125 FC-T de Bosch. Incluye funciones adicionales como Speed Selection, Constant Speed, Soft Start y Overload Protection.                                                                                                                                                                                                                                                    |
| Quantity per pallet                 | 108                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Peso neto                           | 2,920 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Peso bruto                          | 2,920 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| País de origen                      | Alemania                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |



## Beneficios del producto

- New PROtection switch for maximum convenience and immediate power off when switch is released
- Speed Selection for individual speed setting
- With KickBack Control, Restart Protection, Vibration Control side handle, and air inlets at the backside of the tool