

# ESMERIL ANGULAR GWS 30-180 PB

|     |                  |
|-----|------------------|
| SKU | 0601.8G0.1E0-000 |
| EAN | 4059952635651    |



## Alcance de la entrega

|                                                    |   |
|----------------------------------------------------|---|
| Locking nut (1 603 340 040)                        | ✓ |
| Two-hole spanner (1 607 950 048)                   | ✓ |
| Vibration Control auxiliary handle (2 608 900 001) | ✓ |
| Protective cover (1 619 P15 622)                   | ✓ |

## Datos técnicos

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Peso                                  | 5,700                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Plato lijador de goma, Ø              | 180,0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Empuñadura principal                  | Rattail                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Velocidad en vacío                    | 8,500 rpm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Velocidad de giro en vacío, hasta     | 8.500,0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Velocidad de giro en vacío, desde     | 6.500,0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Potencia absorbida                    | 2.800,0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Interruptor                           | PROtection Switch                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Ø del disco                           | 180,0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Ø del cepillo (tipo vaso)             | 100,0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Rosca del husillo portamuela          | M14                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Trades                                | Metal construction                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Versión larga parte 1                 | The GWS 30-180 PB Professional comes with a very powerful 2,800 W brushless motor that allows enduring performance and best material removal results even on demanding jobs. It provides maximum power, high overload capability, and stands for maximum productivity. The brushless motor without commutator and carbon brushes leads to less wear and minimum downtime. User protection is also increased thanks to a brake which enables fast disc standstill, a PROtection switch for immediate power off when releasing the trigger, and KickBack Control. In addition, Vibration Control and an improved vibration cancelling system absorbs most of the vibration while working.                                                                                                           |
| Versión larga parte 2                 | The GWS 30-180 PB Professional grinds metal or welding seams and cuts metal, concrete, bricks, and tiles.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Versión larga parte 3                 | The GWS 30-180 PB Professional features an LED tool status indicator, Overload Protection, Restart Protection, and Soft Start.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Información adicional versión corta   | The GWS 30-180 PB Professional comes with an LED tool status indicator, Overload Protection, Restart Protection, and Soft Start.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Tolerancia K                          | 3,0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Nivel de presión acústica             | 92,500                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Nivel de ruido                        | The A-rated noise level of the power tool is typically as follows: Sound pressure level 92.5 dB(A); Sound power level 103.5 dB(A). Uncertainty K= 3 dB.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Nivel total de vibraciones            | 1,500<br>2,700<br>Lijar con hoja de lija<br>Desbastar superficies (desbastado)<br>5,0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Cordless/Corded                       | Corded                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Versión larga parte 1 (BE)            | El potente motor Brushless sin escobillas de carbón de 2800 W de la GWS 30 PB asegura un aumento de la productividad, un rendimiento duradero y una tasa de eliminación de material muy elevada. Los componentes clave garantizan una larga vida útil y el motor Brushless sin escobillas de carbón reduce el tiempo de inactividad y el desgaste de la herramienta. La alta productividad se suma a las cómodas características de seguridad diseñadas para proteger al operador. La función Vibration Control evita que se produzcan lesiones en las manos a largo plazo. Las funciones de KickBack Control, Soft Start, Restart Protection, un freno de motor integrado y un interruptor PROtection para el apagado inmediato al soltar el gatillo, protegen contra las lesiones accidentales. |
| Nivel de potencia acústica            | 103,500                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Versión larga parte 2 (BE)            | La GWS 30 PB es capaz de rectificar metales o costuras de soldadura y cortar barras de refuerzo, metal y concreto.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Positioning (Headline emotional) (BE) | Revolutionary grinding performance from Bosch's first corded brushless grinder                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Quantity per pallet                   | 48                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Peso neto                             | 7,580 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Peso bruto                            | 7,580 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| País de origen                        | China                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |



## Beneficios del producto

- 2,800 W powerful brushless motor delivers industry-leading material removal rate
- Low maintenance and reduced tool downtime
- Vibration Control prevents long-term damage to hands
- Safety & convenience: KickBack Control, Soft Start, Restart Protection, and braking
- PROtection switch immediately cuts off power when the trigger is released