

GSS 20-18 A Lijadora orbital

SKU	0601.070.1E1-000
EAN	4053423301908



Alcance de la entrega

Cardboard box	✓
1 x punching plate (1 619 PS1 082)	✓
1 x dust bag (1 619 PS1 104)	✓

Datos técnicos

Peso	1,600
Velocidad en vacío	8,000 – 12,000 rpm
Velocidad de giro en vacío, hasta	12.000,0
Velocidad de giro en vacío, desde	8.000,0
Potencia absorbida	200,0
Diámetro de orbitación	2,0
No-load orbital stroke rate	16,000 – 24,000 opm
Número de orbitaciones, hasta	24.000,0
Número de orbitaciones, de	16.000,0
Tolerancia K	3,0
Nivel de presión acústica	76,0
Nivel de ruido	The A-rated noise level of the power tool is typically as follows: Sound pressure level 76 dB(A); Sound power level 84 dB(A). Uncertainty K= 3 dB.
Nivel de potencia acústica	84,0
Quantity per pallet	72
Peso neto	2,100 kg
Peso bruto	2,100 kg

País de origen	China
----------------	-------



Beneficios del producto

- Lessens fatigue thanks to its low vibration value limiting to 3.0 m/s2
- Effortless sanding in any direction with well-balanced design and high comfort from ergonomic, anti-skid grip
- Efficient dust management with 83.5% pick-up rate and detachable bag for easy dust dumping