

LLAVE DE IMPACTO GDS 18V-780

SKU	0601.9P4.0E0-000
EAN	4053423346978



Alcance de la entrega

Cordless impact wrench GDS 18V-780 Professional (0 601 9P4 0E0)	✓
---	---

Datos técnicos

Tensión de la batería	18.0 V
Par de apriete a la potencia útil máxima	780,0
Peso (sin batería)	2,100
Velocidad en vacío	2,000 rpm
Velocidad de giro en vacío, hasta	2.000,0
Impact rate	2,400 bpm
Impact rate (1st level)	1,900 bpm
Impact rate (2nd level)	2,100 bpm
Impact rate (3rd level)	2,400 bpm
Número de impactos, hasta	2.400,0
Portaherramientas (suministrado)	1/2" Square
Información adicional versión corta	The GDS 18V-780 Professional also has ABR for untightening bolts which automatically stops tool and prevents them from dropping
Tolerancia K	3,0
Nivel de presión acústica	108,0
Nivel de ruido	The A-rated noise level of the power tool is typically as follows: Sound pressure level 108 dB(A); Sound power level dB(A). Uncertainty K= 3 dB.
Margen de ajuste del par de giro, máx. 3.er nivel	780,0
Margen de ajuste del par de giro, mín./máx. 2.º nivel	550 Nm
Margen de ajuste del par de giro, máx. 1.er nivel	300,0
Margen de ajuste del par de giro, mín./máx. 3.er nivel	780 Nm
Margen de ajuste del par de giro, mín./máx. 1.er nivel	300 Nm
Margen de ajuste del par de giro, máx. 2.º nivel	550,0
Quantity per pallet	120
Peso neto	2,500 kg
Peso bruto	2,500 kg

País de origen	China
----------------	-------

Beneficios del producto

- Tackles tough bolting work with ease thanks to high tightening torque of 780 Nm and untightening torque of 1000 Nm
- Compact design with short 170 mm head length is ideal for working in narrow spaces
- Durable and robust with ½” tool holder and an extra protection ring that reduces stress by 20%
- Handles many applications thanks to multiple operating modes

