GIS 500: pirómetro digital (Láser)


SKU	0601.083.4G0-000
EAN	3165140978477



Alcance de la entrega

1 x 1.5 V LR6 battery (AA)	✓
Pouch	✓

Datos técnicos



Operating temperature	-5 – 50°C
Temperatura de servicio, hasta	50,0
Temperatura de servicio, desde	-5,0
Peso	0,220
Altura	54,0
Longitud	101,0
Storage temperature	-20 – 70°C
Temperatura de almacenamiento, hasta	70,0
Temperatura de almacenamiento, desde	-20,0
Diodo láser	635 nm
Exactitud de medición IR	± 1.8 °C
Exactitud de la medición (habitual)	0 ℃ ≤ t 100 ℃: ±1.8 ℃ Surface temperature -10 ℃ t 0 ℃: ± 2.8 ℃ -30 ℃ ≤ t ≤ -10 ℃: ± (1.8 ℃ + 0.1 x |t| ℃) 100 ℃ ≤ t ≤ 500 ℃: ± 1.8%
Alimentación de tensión y tiempo de funcionamiento	2 x 1.5V LR6 (AA) batteries, 9h
Length x width x height	171 mm
Versión larga parte 1	La herramienta de medición no debe utilizarse con fines médicos.
Measuring application	Spot temperature measurement
Width	171,0
Quantity per pallet	225
Peso neto	0,510 kg
Peso bruto	0,510 kg

País de origen	China

Beneficios del producto

- Simple – Immediate measuring results at one simple press with the selection of 3 emissivity gradings for more precise measurement
- Compact - Easy to carry around thanks to the ergonomic housing design with carrying pouch
- Versatile - Wide temperature measurement range for extreme conditions with press and hold continuous measuring function