

GCO 14 - 24

SKU	0601.B37.0E0-000
EAN	3165140837293



Alcance de la entrega

1 x cutting disc, Expert for Metal, 355 x 25.4 mm (2 608 600 543)	✓
---	---

Datos técnicos

Peso	17,500
Tool dimensions (width x length x height)	256 x 520 x 400 mm
Velocidad en vacío	3.800,0
Potencia absorbida	2.400,0
Cutting capacity at L-profile 0º	130 x 130 mm
Cutting capacity at L-profile 0º, width	130,0
Cutting capacity at L-profile 0º, height	130,0
Cutting capacity at L-profile 45º mitre	115 x 115 mm
Capacidad de corte de perfil en L a 45° de inglete, anchura	115,0
Capacidad de corte de perfil en L a 45° de inglete, altura	115,0
Cutting capacity at rectangle 0º	100 x 196 mm
Cutting capacity at rectangle 0º, width	196,0
Cutting capacity at rectangle 0º, height	100,0
Cutting capacity at rectangle 45º mitre	107 x 115 mm
Capacidad de corte rectangular a 45° de inglete, anchura	115,0
Capacidad de corte rectangular a 45° de inglete, altura	107,0
Cutting capacity at square 0º	119 x 119 mm
Cutting capacity at square 0º, width	119,0
Cutting capacity at square 0º, height	119,0
Cutting capacity at square 45º mitre	110 x 110 mm
Capacidad de corte de cuadrado macho a 45° de inglete, anchura	110,0
Capacidad de corte de cuadrado macho a 45° de inglete, altura	110,0
Diámetro interior del disco de tronzar	25,400
Diámetro del disco de tronzar	355,0
Tolerancia K	3,0
Nivel de presión acústica	100,500
Nivel de ruido	The A-rated noise level of the power tool is typically as follows: Sound pressure level 100.5 dB(A); Sound power level 113 dB(A). Uncertainty K= 3 dB.
Nivel de potencia acústica	113,0
Quantity per pallet	12
Peso neto	17,700 kg
Peso bruto	17,700 kg

HEAVY
DUTY



Beneficios del producto

- High overload capacity for the toughest applications
- Advanced support for cutting materials
- Ultimate operator protection and wobbling minimization